

# Manual Supplement

Manual Title:	Index 2XL Users	Supplement Issue:	4
Part Number:	2226196	Issue Date:	2/11
Print Date:	April 2007	Page Count:	2
Revision/Date:			

---

---

This supplement contains information necessary to ensure the accuracy of the above manual.

## Change #1, 47809

On page D-1, under **Battery Life**, add the following section:

**Battery Charger**.....Lead Acid Battery Charger Only

Input.....100-250 V , 50-60 Hz, 0.3 A

Output.....+12 V DC, 0.5 A

*Note*

*For best battery life, turn the unit off when not in use.*

## Change #2

On page 5-2, under **Verified Oximeter Makes**:

Add: Masimo

Delete: HP® (Merlin)

Nonin

Novamatrix®

## Change #3, 49765

On page D-1, under **Equipment Specifications**, add the following:

Operating Temperature.....15 °C to 35 °C (59 °F to 95 °F)

Storage Temperature.....0 °C to 50 °C (32 °F to 122 °F)

## Change #4



On pages 1-3 and 1-4, delete the entire section of the **Electromagnetic Interference and Susceptibility**.

On page 1-3 following the **Precautions** section add the following:

### Symbols

Table 1 lists and describes the symbols used on the Simulator and in this manual.

**Table 1. Symbols**

Symbol	Description	Symbol	Description
⎓	DC (Direct Current or Voltage)		Important Information; refer to manual
	Do not dispose of this product as unsorted municipal waste. Go to Fluke's website for recycling information.	CE	Conforms to European Union directives

## **Cleaning**

### **⚠ Caution**

**To avoid damage to the Simulator, do not allow liquids to enter any enclosure opening.**

To clean the Simulator, wipe the surfaces with a damp cloth. Do not spray cleaning agents onto the Simulator.

Inspect the rear-panel connectors for dust and contamination. Use a compressed gas (air) duster, approved for use on computers and sensitive electronic equipment to remove any dust build up. Avoid directing excessive compressed air into enclosure openings.

## **Change #5, 57484**

On page D-1, Under **Equipment Specifications** add the following:

Weight.....2.38 kg (5.2 lbs)

Size.....26.4 cm x 25.4 cm x 10.2 cm (10.4 in x 10 in x 4 in)